'C' Service: Truck & trailer

200,000km (or recommended interval as noted) or 12 months (whichever comes first) NOTE: Areas which do not relate to the particular Vehicle are to be marked NA. These are generic schedules **ONLY**. Contact your vehicle manufacturer for specific servicing schedule requirements for the make and model of your vehicle. Repairer: Vehicle description: Rego: ____ Odometer: Yes NA All components of 'A' Service check off Change: Change oil in oil filled wheel bearings Service air dryers where applicable Check: Thorough inspection of vehicle by a suitably qualified and experienced person Oil changes due Mileage book Power steering oil and filter Date for air filter replacement Valves. Inspect and adjust where required Truck's tractor protection Alternator brushes for wear For coolant change/24 months Truck and trailer for tools, triangles, extinguisher and spares etc. Re torque all "U" bolts and cross members Vehicle speed limiting equipment for tampering and accuracy. A GPS verification process will meet the requirements of the TruckSafe standards, as will an OEM certificate or the use of company speed management data A speed limiter will not prevent speeding if a truck is travelling downhill, and the check must take this into account. Injectors, rebuild or replace (at intervals between 300,000 and 600,000 km, dependent on vehicle use or manufacturers recommendation) Injector Pump, Adjust and or rebuild (at intervals between 500,00 and 800,000 km, dependent on vehicle use or manufacturers recommendation) Injection timing, check and set (at intervals between 250,000 and 400,000km,

ALL FLUID LEVELS, LUBRICANT SPECIFICATIONS, INSPECTIONS, ADJUSTMENTS AND REPAIRS MUST MEET THE RELEVANT MANUFACTURES REQUIREMENTS



dependent on vehicle use or manufacturers recommendation)

Note all Faults:		
Mechanic Sign:	Print name:	

